

# JOYALL TIRES



**JOYALL**  
PROFESSION SAFETY AND  
DURABILITY ORIGIN OF JOYALL TIRES **TIRES**



2020





Tire Size	PR	Pattern	Pattern Description	Tread Depth		Rim	Tube Type	Load Index	Spd	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(Kpa)		Load Capacity(Kg)	
				mm	1/32Inch							Single	Dual	Single	Dual
315/80R22.5	18	A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	154/151	M	1070	316	830	830	3750	3450
315/80R22.5	20	A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	157/154	L	1070	316	900	900	4125	3750
315/80R22.5	20	A606/A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	157/154	L	1070	316	900	900	4125	3750
315/80R22.5	20	A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	157/154	L	1076	316	900	900	4125	3750
315/80R22.5	20	A702	FREEWAY DRIVE	24.8	31.2	9.00	TL	157/154	K	1090	316	900	900	4125	3750
315/80R22.5	20	A802	ON OFF DRIVE	24.5	30.9	9.00	TL	157/154	J	1080	316	900	900	4125	3750
315/80R22.5	18	G836/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	154/151	M	1067	312	830	830	3750	3450
315/80R22.5	20	G836/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	157/154	L	1067	312	900	900	4125	3750
315/80R22.5	20	G836/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	157/154	L	1076	310	900	900	4125	3750
315/80R22.5	20	A603/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	157/154	L	1067	312	900	900	4125	3750
315/80R22.5	20	A888+	FREEWAY DRIVE	24.0	30.2	9.00	TL	157/154	K	1080	316	900	900	4125	3750
315/80R22.5	18	B875	REGIONAL TRAILER	16.0	20.2	9.00	TL	154/151	M	1076	310	830	830	3750	3450
315/80R22.5	20	B875	REGIONAL TRAILER	16.0	20.2	9.00	TL	157/154	L	1076	310	900	900	4125	3750
315/80R22.5	18	B878/G828	FREEWAY DRIVE	22.0	27.7	9.00	TL	154/151	M	1081	312	830	830	3750	3450
315/80R22.5	20	B878/G828	FREEWAY DRIVE	22.0	27.7	9.00	TL	157/154	L	1081	312	900	900	4125	3750
315/80R22.5	20	B878/G828	FREEWAY DRIVE	22.0	27.7	9.00	TL	157/154	L	1081	308	900	900	4125	3750
385/65R22.5	20	A601	FREEWAY TRAILER	18.5	23.3	11.75	TL	160	K	1073.4	386	900	-	4500	-
385/65R22.5	24	A601	FREEWAY TRAILER	18.5	23.3	11.75	TL	164	J	1073.4	386	900	-	5000	-
385/65R22.5	20	A610	FREEWAY TRAILER	17.5	22.0	11.75	TL	160	K	1071.4	386	900	-	4500	-
385/65R22.5	24	A610	FREEWAY TRAILER	17.5	22.0	11.75	TL	164	J	1071.4	386	900	-	5000	-

STEER / TRAILER



MID-LONG HAUL

DRIVE



MID-LONG HAUL

ON & OFF

ALL POSITION



MID-LONG HAUL

REGIONAL

OFF ROAD

BUS



# MID-LONG HAUL

STEER/ TRAILER	A608	A609
	A605	A876
	A875	A8
DRIVE	A601	A610
	A878	B878
	A888	A88
ALL POSITION	A702	
	A889	A505


Tire Size	PR	Pattern	Pattern Description	Tread Depth		Rim	Tube Type	Load Index Single/Dual	Spd	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(Kpa)		Load Capacity(Kg)	
				mm	1/32Inch							Single	Dual	Single	Dual
11R24.5	14	G836/A876	FREEWAY TRAILER	14.8	18.6	8.25	TL	146/143	L	1092.6	268	720	720	3000	2725
11R24.5	16	G836/A876	FREEWAY TRAILER	14.8	18.6	8.25	TL	149/146	L	1092.6	268	830	830	3250	3000
11R24.5	14	A878	FREEWAY DRIVE	21.5	27.1	8.25	TL	146/143	L	1106	268	720	720	3000	2725
11R24.5	16	A878	FREEWAY DRIVE	21.5	27.1	8.25	TL	149/146	L	1106	268	830	830	3250	3000
12R22.5	18	A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	152/149	L	1081	293	930	930	3550	3250
12R22.5	18	A88	FREEWAY DRIVE	22.0	27.7	9.00	TL	152/149	L	1089	293	930	930	3550	3250
12R22.5	18	A501	BUS DRIVE	21.5	27.1	9.00	TL	152/149	L	1092	305	930	930	3550	3250
12R22.5	18	A605	FREEWAY STEER	17.0	21.4	9.00	TL	152/149	L	1082	290	930	930	3550	3250
12R22.5	18	A608	FREEWAY STEER	17.0	21.4	9.00	TL	152/149	L	1084	296	930	930	3550	3250
12R22.5	18	A609	FREEWAY TRAILER	15.3	19.3	9.00	TL	152/149	L	1080	290	930	930	3550	3250
12R22.5	18	A803	ON OFF DRIVE	23.0	29.0	9.00	TL	152/149	K	1094	293	930	930	3550	3250
12R22.5	18	A875/T800/T810	FREEWAY TRAILER	15.2	19.1	9.00	TL	152/149	L	1074	290	930	930	3550	3250
12R22.5	18	G836/A876	FREEWAY TRAILER	16.2	20.4	9.00	TL	152/149	L	1074	290	930	930	3550	3250
12R22.5	18	E800/A889	FREEWAY TRAILER	16.5	20.8	9.00	TL	152/149	L	1075	290	930	930	3550	3250
12R22.5	18	A919	REGIONAL TRAILER	16.5	20.8	9.00	TL	152/149	L	1081	293	930	930	3550	3250
12R22.5	18	A928	ON OFF DRIVE	24.0	30.2	9.00	TL	152/149	K	1096	293	930	930	3550	3250
12R22.5	18	A958/A801	ON OFF DRIVE	19.0	23.9	9.00	TL	152/149	K	1085	293	930	930	3550	3250
12R22.5	18	B875/T801/T811	REGIONAL TRAILER	15.0	18.9	9.00	TL	152/149	L	1074	290	930	930	3550	3250
12R22.5	12	B875	REGIONAL TRAILER	15.0	18.9	9.00	TL	143/141	L	1074	290	620	620	2725	2575
12R22.5	18	G828/B878	FREEWAY DRIVE	22.0	27.7	9.00	TL	152/149	L	1086	290	930	930	3550	3250
12R22.5	18	C958	ON OFF DRIVE	18.5	23.3	9.00	TL	152/149	K	1080	290	930	930	3550	3250
13R22.5	20	A9	REGIONAL ALL	17.0	21.4	9.75	TL	156/153	K	1120	316	930	930	4000	3650
13R22.5	18	A889	FREEWAY TRAILER	16.5	20.8	9.75	TL	154/151	K	1115	308	830	830	3750	3450
13R22.5	20	A889	FREEWAY TRAILER	16.5	20.8	9.75	TL	156/153	K	1115	308	930	930	4000	3650
13R22.5	20	A958	ON OFF DRIVE	19.0	23.9	9.75	TL	156/153	K	1124	316	930	930	4000	3650
275/70R22.5	16	A501	BUS DRIVE	22.5	28.3	8.25	TL	148/145	J	962	280	900	900	3150	2900
275/70R22.5	18	A503	BUS STEER	22.0	27.7	8.25	TL	150/145	J	962	280	900	900	3350	2900
295/75R22.5	16	G835/A875	FREEWAY TRAILER	11.0	13.9	9.00	TL	146/143	L	998	288	830	830	3000	2725
295/75R22.5	16	G836/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	146/143	L	1006	288	830	830	3000	2725
295/75R22.5	16	A878	FREEWAY DRIVE	22.0	27.7	9.00	TL	146/143	L	1020	288	830	830	3000	2725
285/75R24.5	14	G846/A876/A866	FREEWAY TRAILER	14.5	18.3	8.25	TL	144/141	L	1046	272	760	760	2800	2575
285/75R24.5	16	G846/A876/A866	FREEWAY TRAILER	14.5	18.3	8.25	TL	147/144	L	1046	272	830	830	3075	2800
285/75R24.5	14	G848/A878	FREEWAY DRIVE	21.5	27.1	8.25	TL	144/141	L	1059	272	760	760	2800	2575
285/75R24.5	16	G848/A878	FREEWAY DRIVE	21.5	27.1	8.25	TL	147/144	L	1059	272	830	830	3075	2800
295/80R22.5	16	A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	150/147	M	1042	295	830	830	3350	3075
295/80R22.5	18	A8	FREEWAY TRAILER	16.5	20.8	9.00	TL	152/149	M	1042	295	900	900	3550	3250
295/80R22.5	16	G836/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	152/148	M	1039	295	850	850	3550	3150
295/80R22.5	18	G836/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	152/149	M	1039	295	900	900	3550	3250
295/80R22.5	18	A602/A876	FREEWAY TRAILER	15.0	18.9	9.00	TL	152/149	M	1039	295	900	900	3550	3250
295/80R22.5	18	A903	MINE DRIVE	21.0	26.5	9.00	TL	152/149	K	1052	295	900	900	3550	3250
295/80R22.5	18	A928/D902	ON OFF DRIVE	21.0	26.5	9.00	TL	152/149	K	1050	295	900	900	3550	3250
295/80R22.5	16	G828/B878	FREEWAY DRIVE	22.0	27.7	9.00	TL	152/148	M	1053	295	850	850	3550	3150
295/80R22.5	18	G828/B878	FREEWAY DRIVE	22.0	27.7	9.00	TL	152/149	M	1053	295	900	900	3550	3250
295/80R22.5	16	A701/B878	FREEWAY DRIVE	22.0	27.7	9.00	TL	152/148	M	1053	295	850	850	3550	3150
295/80R22.5	18	A701/B878	FREEWAY DRIVE	22.0	27.7	9.00	TL	152/149	M	1053	295	900	900	3550	3250



Tire Size	PR	Pattern	Pattern Description	Tread Depth		Rim	Tube Type	Load Index Single/Dual	Spd	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(Kpa)		Load Capacity(Kg)	
				mm	1/32Inch							Single	Dual	Single	Dual
7.50R16LT	14	B875	REGIONAL TRAILER	13.0	16.4	6.00	TT	122/118	L	803	212	670	670	1500	1320
9.00R20	16	A66+	MINE SOFT&HARD	24.5	30.9	7.00	TT	144/142	D	1032	260	900	900	2800	2650
10.00R20	16	A9	REGIONAL ALL	16.0	20.2	7.50	TT	146/143	K	1054	278	830	830	3000	2725
10.00R20	18	A9	REGIONAL ALL	16.0	20.2	7.50	TT	149/146	K	1054	278	930	930	3250	3000
10.00R20	16	A66+	MINE SOFT&HARD	24.5	30.9	7.50	TT	146/143	D	1068	278	830	830	3000	2725
10.00R20	18	A66+	MINE SOFT&HARD	24.5	30.9	7.50	TT	149/146	D	1068	278	930	930	3250	3000
10.00R20	16	A958	ON OFF DRIVE	18.0	22.7	7.50	TT	146/143	K	1058	278	830	830	3000	2725
10.00R20	18	A958	ON OFF DRIVE	18.0	22.7	7.50	TT	149/146	K	1058	278	930	930	3250	3000
10.00R20	16	B958	ON OFF DRIVE	21.8	27.5	7.50	TT	146/143	J	1064	278	830	830	3000	2725
10.00R20	18	B958	ON OFF DRIVE	21.8	27.5	7.50	TT	149/146	J	1064	278	930	930	3250	3000
11.00R20	16	A9	REGIONAL ALL	16.5	20.8	8.00	TT	150/147	K	1080	286	830	830	3350	3075
11.00R20	18	A9	REGIONAL ALL	16.5	20.8	8.00	TT	152/149	K	1080	286	930	930	3550	3250
11.00R20	18	A66+	MINE SOFT&HARD	25.0	31.5	8.00	TT	152/149	D	1088	286	930	930	3550	3250
11.00R20	18	A669/E610/E611	MINE DRIVE	24.0	30.2	8.00	TT	152/149	D	1092	282	930	930	3550	3250
11.00R20	18	A958	ON OFF DRIVE	19.0	23.9	8.00	TT	152/149	K	1085	286	930	930	3550	3250
11.00R20	18	A959	REGIONAL TRAILER	15.0	18.9	8.00	TT	152/149	K	1078	282	930	930	3550	3250
11.00R20	18	B958/D915	ON OFF DRIVE	21.0	26.5	8.00	TT	152/149	J	1080	286	930	930	3550	3250
11.00R20	18	C958/D901	ON OFF DRIVE	18.5	23.3	8.00	TT	152/149	K	1080	284	930	930	3550	3250
11.00R20	18	D909/D900	ON OFF DRIVE	18.5	23.3	8.00	TT	152/149	K	1080	284	930	930	3550	3250
12.00R20	18	A9	REGIONAL ALL	17.0	21.4	8.50	TT	154/151	K	1120	310	830	830	3750	3450
12.00R20	20	A9/E900/A502	REGIONAL ALL	17.0	21.4	8.50	TT	156/153	K	1120	310	900	900	4000	3650
12.00R20	20	A66+	MINE SOFT&HARD	24.0	30.2	8.50	TT	156/153	D	1130	310	900	900	4000	3650
12.00R20	18	A669/E610/E611	MINE DRIVE	25.0	31.5	8.50	TT	154/151	D	1130	306	830	830	3750	3450
12.00R20	20	A669/E610/E611	MINE DRIVE	25.0	31.5	8.50	TT	156/153	D	1130	306	900	900	4000	3650
12.00R20	18	A958	ON OFF DRIVE	19.0	23.9	8.50	TT	154/151	K	1124	310	830	830	3750	3450
12.00R20	20	A958	ON OFF DRIVE	19.0	23.9	8.50	TT	156/153	K	1124	310	900	900	4000	3650
12.00R20	18	B958/D915	ON OFF DRIVE	22.0	27.7	8.50	TT	154/151	J	1121	310	830	830	3750	3450
12.00R20	20	B958/D915	ON OFF DRIVE	22.0	27.7	8.50	TT	156/153	J	1121	310	900	900	4000	3650
12.00R20	18	C958/D901	ON OFF DRIVE	18.6	23.4	8.50	TT	154/151	K	1115	308	830	830	3750	3450
12.00R20	20	C958/D901/A806	ON OFF DRIVE	18.6	23.4	8.50	TT	156/153	K	1115	308	900	900	4000	3650
12.00R20	18	D900/D909	ON OFF DRIVE	20.6	26.0	8.50	TT	154/151	K	1119	308	830	830	3750	3450
12.00R20	20	D900/D909	ON OFF DRIVE	20.6	26.0	8.50	TT	156/153	K	1119	308	900	900	4000	3650
12.00R24	18	A505	FREWAY TRAILER	18.0	22.7	8.50	TT	158/155	K	1226	308	830	830	4250	3875
12.00R24	20	A505	FREWAY TRAILER	18.0	22.7	8.50	TT	160/157	K	1226	308	900	900	4500	4125
12.00R24	18	A807	ON OFF DRIVE	19.5	24.6	8.50	TT	158/155	K	1229	308	830	830	4250	3875
12.00R24	20	A807	ON OFF DRIVE	19.5	24.6	8.50	TT	160/157	K	1229	308	900	900	4500	4125
11R22.5	16	A8	FREWAY TRAILER	16.5	20.8	8.25	TL	146/143	L	1050	272	830	830	3000	2725
11R22.5	16	A501	BUS DRIVE	22.0	27.7	8.25	TL	148/145	J	1060	282	830	830	3150	2900
11R22.5	16	A805	ON OFF DRIVE	23.0	29.0	8.25	TL	148/145	K	1062	276	830	830	3150	2900
11R22.5	16	G835/A875	FREWAY TRAILER	11.0	13.9	8.25	TL	146/143	L	1039	272	830	830	3000	2725
11R22.5	16	G836/A876	FREWAY TRAILER	15.0	18.9	8.25	TL	146/143	L	1047	272	830	830	3000	2725
11R22.5	16	A878	FREWAY DRIVE	22.0	27.7	8.25	TL	146/143	L	1061	272	830	830	3000	2725
11R22.5	16	B875/T801/T811	REGIONAL TRAILER	15.0	18.9	8.25	TL	146/143	L	1047	272	830	830	3000	2725
11R22.5	16	G828/B878	FREWAY DRIVE	22.0	27.7	8.25	TL	146/143	L	1061	272	830	830	3000	2725
11R22.5	16	A503	BUS STEER	22.0	27.7	8.25	TL	148/145	J	1060	282	830	830	3150	2900



**NEW MODEL-  
A608**



Suitable for steer and trailer position  
Designed for mid-long distance transportation on paved road at high speed

- Improved tread design effectively reduce rolling resistance and enhance fuel economy
- Close shoulder design improves directional driving experience, anti-skid and prevents uneven wear
- Stone ejector at groove bottom improves self-cleaning ability, enhances puncture-resistance
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth mm	1/32 Inch	Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa) Single	Dual	Load Capacity(kg) Single	Dual
12R22.5	18	FREWAY STEER	17.00	21.4	9.00	TL	152/149L	1084	296	930	930	3550	3250



**NEW MODEL-  
A609**




Suitable for trailer position  
Designed for mid-long distance transportation on paved road at high speed

- Straight grooves effectively reduce rolling resistance and enhance fuel economy
- Close shoulder design improves directional driving experience, anti-skid and prevents uneven wear
- Stone ejector at groove bottom improves self-cleaning ability, enhances puncture-resistance
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth mm	1/32 Inch	Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa) Single	Dual	Load Capacity(kg) Single	Dual
12R22.5	18	FREWAY STEER	15.30	19.3	9.00	TL	152/149L	1084	296	930	930	3550	3250



**NEW MODEL-  
A605**



Suitable for trailer position  
Designed for mid-long distance transportation on paved road at high speed


- Straight grooves effectively reduce rolling resistance and enhance fuel economy
- Close shoulder design improves directional driving experience, anti-skid and prevents uneven wear
- Stone ejector at groove bottom improves self-cleaning ability, enhances puncture-resistance
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth mm	1/32 Inch	Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa) Single	Dual	Load Capacity(kg) Single	Dual
12R22.5	18	FREWAY STEER	17.00	21.4	9.00	TL	152/149L	1084	296	930	930	3550	3250





**TYPE MODEL-**  
**A876**




Suitable for trailer positions  
Designed for mid-long distance transportation on paved road at high speed

- Four longitudinal grooves effectively reduce rolling-resistance and enhance fuel economy
- Close shoulder design improves directional driving experience, anti-skid and prevents uneven wear
- Small grooves on pattern blocks effectively improve crown heat emission
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	14	FREWAY TRAILER	15.00	18.9	8.25	TL	144/142L	1049	272	720	720	2800	2650
11R22.5	16	FREWAY TRAILER	15.00	18.9	8.25	TL	146/143L	1047	272	830	830	3000	2725
11R24.5	14	FREWAY TRAILER	14.80	18.6	8.25	TL	146/143L	1093	268	720	720	3000	2725
11R24.5	16	FREWAY TRAILER	14.80	18.6	8.25	TL	149/146L	1093	268	830	830	3250	3000
295/75R22.5	14	FREWAY TRAILER	15.00	18.9	9.00	TL	144/141L	1024	290	830	830	2800	2575
295/75R22.5	16	FREWAY TRAILER	15.00	18.9	9.00	TL	146/143L	1006	288	850	850	3000	2725
285/75R24.5	14	FREWAY TRAILER	14.50	18.3	8.25	TL	144/141L	1046	272	760	760	2800	2575
285/75R24.5	16	FREWAY TRAILER	14.50	18.3	8.25	TL	147/144L	1046	272	830	830	3075	2800
12R22.5	18	FREWAY TRAILER	16.20	20.4	9.00	TL	152/149L	1074	290	930	930	3550	3250
295/80R22.5	16	FREWAY TRAILER	15.00	18.9	9.00	TL	152/148M	1039	295	830	830	3350	3150
295/80R22.5	18	FREWAY TRAILER	15.00	18.9	9.00	TL	152/149M	1039	295	830	830	3350	3250
315/80R22.5	18	FREWAY TRAILER	15.00	18.9	9.00	TL	154/151M	1067	312	830	830	3750	3450
315/80R22.5	20	FREWAY TRAILER	15.00	18.9	9.00	TL	157/154L	1067	312	900	900	4125	3750



**TYPE MODEL-**  
**A875**



Suitable for trailer position  
Designed for mid-long distance transportation on paved road at high speed

- Four longitudinal grooves effectively reduce rolling-resistance and enhances fuel economy
- Close shoulder design improves directional driving experience, anti-skid and prevents uneven wear
- Small grooves on pattern blocks effectively improve crown heat emission
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	14	FREWAY TRAILER	11.00	13.9	8.25	TL	144/142L	1039	272	720	720	2800	2650
11R22.5	16	FREWAY TRAILER	11.00	13.9	8.25	TL	146/143L	1039	272	830	830	3000	2725
295/75R22.5	14	FREWAY TRAILER	11.00	13.9	9.00	TL	144/141L	998	288	720	720	2800	2650
295/75R22.5	16	FREWAY TRAILER	11.00	13.9	9.00	TL	146/143L	998	288	830	830	3000	2725
12R22.5	18	FREWAY TRAILER	15.20	19.1	9.00	TL	152/149L	1074	290	930	930	3550	3250



**NEW** **RECOMMENDED**  
**A501**




Suitable for drive position  
Designed for mid-short distance bus or coach on paved road at mid-low speed

- >
- >
- >

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	16	BUS DRIVE	22.00	27.7	8.25	TL	148/145J	1060	282	830	830	3150	2900
12R22.5	18	BUS DRIVE	21.5	27.1	9.00	TL	152/149L	1092	305	930	930	3550	3250
275/70R22.5	16	BUS DRIVE	22.50	28.3	8.25	TL	148/145J	962	280	900	900	3150	2900



**NEW** **MODEL-**  
**A503**



Suitable for all position  
Designed for mid-short distance bus or coach on paved road at mid-low speed

- >
- >
- >

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	16	BUS STEER	22.00	27.7	8.25	TL	148/145J	1060	282	830	830	3150	2900
275/70R22.5	18	BUS STEER	22.00	27.7	8.25	TL	150/145J	962	280	900	900	3350	2900

**OTHER CHOICES**



**A8**



**A876**





**BUS**

A501

A503

A8

A876



**TYPE MODEL-**

**A8**



Suitable for trailer position  
Designed for mid-long distance transportation on paved road at high speed

- Straight grooves effectively reduce rolling resistance and enhance fuel economy
- Close shoulder design improves directional driving experience, anti-skid and prevents uneven wear
- Stone ejector at groove bottom improves self-cleaning ability, enhances puncture-resistance
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	16	FREEWAY TRAILER	16.50	20.8	8.25	TL	146/143L	1050	272	830	830	3000	2725
12R22.5	18	FREEWAY TRAILER	16.50	20.8	9.00	TL	152/149L	1081	293	930	930	3550	3250
295/80R22.5	18	FREEWAY TRAILER	16.50	20.8	9.00	TL	152/149M	1042	295	900	900	3550	3250
315/80R22.5	20	FREEWAY TRAILER	16.50	20.8	9.00	TL	157/154L	1070	316	900	900	4125	3750
315/80R22.5	20	FREEWAY TRAILER	16.50	20.8	9.00	TL	157/154L	1076	316	900	900	4125	3750



**TYPE MODEL-**

**A601**



Suitable for trailer positions  
Designed for mid-long distance transportation on paved road at mid-low speed

- Four longitudinal zigzag grooves design provides excellent high speed and anti-skidding performance
- Widened pattern design, optimized cap profile, high durable tread formula for superior service life, cost-effective
- Zigzag grooves design, enhancing puncture resistance, reducing groove crack
- Low heat generation recipe, high-tensile casing steel cord structure design, superior durability, retreadability

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
385/65R22.5	20	FREEWAY TRAILER	18.5	23.3	11.75	TL	160K	1073.4	386	900	-	4500	-
385/65R22.5	24	FREEWAY TRAILER	18.5	23.3	11.75	TL	164J	1073.4	386	900	-	5000	-



**NEW MODEL-**

**A610**



Suitable for trailer positions  
Designed for mid-long distance transportation on paved road at mid-low speed

- Four longitudinal zigzag grooves design provides excellent high speed and anti-skidding performance
- Widened pattern design, optimized cap profile, high durable tread formula for superior service life, cost-effective
- Zigzag grooves design, enhancing puncture resistance, reducing groove crack
- Low heat generation recipe, high-tensile casing steel cord structure design, superior durability, retreadability

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
385/65R22.5	20	FREEWAY TRAILER	17.5	22.0	11.75	TL	160K	1071.4	386	900	-	4500	-
385/65R22.5	24	FREEWAY TRAILER	17.5	22.0	11.75	TL	164J	1071.4	386	900	-	5000	-





**TYPE MODEL-**  
**A889**



Suitable for trailer positions  
Designed for mid-long distance transportation on paved road at high speed

- > Three zigzag pattern design provides excellent driving and braking ability
- > Strong pattern block, more suitable for mixed road conditions
- > High strength casing steel cord and reinforced bead provide excellent light load transportation performance
- > Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	FREEWAY TRAILER	16.50	20.8	9.00	TL	152/149L	1075	290	930	930	3550	3250
13R22.5	18	FREEWAY TRAILER	16.50	20.8	9.75	TL	154/151K	1115	308	830	830	3750	3450
13R22.5	20	FREEWAY TRAILER	16.50	20.8	9.75	TL	156/153K	1115	308	930	930	4000	3650



**NEW MODEL-**  
**A903**



Suitable for drive positions of dumper  
Designed for short distance heavy load transportation on rough roads

- > Big lateral block pattern provides powerful driving and grip ability
- > Deepened groove design and optimized tread formula provide excellent wear, cut and tear resistance performance.
- > Reinforced bead design provides excellent loading capacity.
- > Stone ejector at bottom of groove provides self-cleaning ability and prevents crown cut.
- > Widened and thickened curbing rib on sidewall effectively prevents sidewall damage.

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
295/80R22.5	18	MINE DRIVE	21.00	26.5	9.00	TL	152/149K	1052	298	900	900	3550	3250



**NEW MODEL-**  
**A505**



Suitable for All position  
Designed for mid-long distance transportation on paved road at high speed

- > Three zigzag pattern design provides excellent driving and braking ability
- > Strong pattern block, more suitable for mixed road conditions
- > High strength casing steel cord and reinforced bead provide excellent light load transportation performance
- > Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12.00R24	18	FREEWAY TRAILER	18.00	22.7	8.50	TT	158/155K	1226	308	830	830	4250	3875
12.00R24	20	FREEWAY TRAILER	18.00	22.7	8.50	TT	160/157K	1226	308	900	900	4500	4125



**TYPE MODEL-**  
**A905**



Suitable for drive positions of dumper  
Designed for short distance heavy load transportation on soft mine road at low speed

- > Contiguous deep lateral big block pattern provides powerful driving and braking ability/ Lateral grooves with wide angles design
- > Thickened groove bottom enhances puncture resistance on unpaved road > Reinforced shoulder increases rigidity of pattern blocks
- > Optimized tread formula provides excellent cut-resistance and tear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
9.00R20	16	MINE DRIVE	24.50	30.9	7.00	TT	144/142D	1032	260	900	900	2800	2650
10.00R20	16	MINE DRIVE	24.50	30.9	7.50	TT	146/143D	1068	278	830	830	3000	2725
10.00R20	18	MINE DRIVE	24.50	30.9	7.50	TT	149/146D	1068	278	930	930	3250	3000
11.00R20	18	MINE DRIVE	25.00	31.5	8.00	TT	152/149D	1088	286	930	930	3550	3250
12.00R20	20	MINE DRIVE	24.00	30.2	8.50	TT	156/153D	1130	310	900	900	4000	3650





**TYPE MODEL-**  
**A66+**



Suitable for drive positions of dumper  
Designed for short distance heavy load transportation on soft mine road at low speed

- Contiguous deep lateral big block pattern provides powerful driving and braking ability/ Lateral grooves with wide angles design
- Thickened groove bottom enhances puncture resistance on unpaved road > Reinforced shoulder increases rigidity of pattern blocks
- Optimized tread formula provides excellent cut-resistance and tear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
9.00R20	16	ON OFF DRIVE	24.50	30.9	7.00	TT	144/142D	1032	260	900	900	2800	2650
10.00R20	16	ON OFF DRIVE	24.50	30.9	7.50	TT	146/143D	1068	278	830	830	3000	2725
10.00R20	18	ON OFF DRIVE	24.50	30.9	7.50	TT	149/146D	1068	278	930	930	3250	3000
11.00R20	18	ON OFF DRIVE	25.00	31.5	8.00	TT	152/149D	1088	286	930	930	3550	3250
12.00R20	20	ON OFF DRIVE	24.00	30.2	8.50	TT	156/153D	1130	310	900	900	4000	3650



**TYPE MODEL-**  
**A669**




Suitable for drive positions of dumper  
Designed for short distance heavy load transportation on hard mine road at low speed

- Contiguous deep lateral big block pattern provides powerful driving and braking ability/ Lateral grooves with wide angles increases
- Stone ejector at groove bottom avoids crown cut
- Reinforced crown adds one extra layer of steel cord, improve impact resistance
- Thickened curbing ribs on sidewalls effectively prevent sidewall damage
- Optimized tread formula provides excellent cut-resistance and tear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11.00R20	18	MINE DRIVE	24.00	30.2	8.00	TT	152/149D	1092	282	930	930	3550	3250
12.00R20	18	MINE DRIVE	25.00	31.5	8.50	TT	154/151D	1130	306	830	830	3750	3450
12.00R20	20	MINE DRIVE	25.00	31.5	8.50	TT	156/153D	1130	306	900	900	4000	3650



**TYPE MODEL-**  
**A878 /G848**




Suitable for drive position  
Designed for mid-long distance transportation on paved road at high speed

- Strong pattern block provides excellent driving and braking ability, more suitable for mix road conditions
- Stone ejector on groove bottom enhances puncture-resistance
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	14	FREEWAY DRIVE	22.00	27.7	8.25	TL	144/142L	1061	272	720	720	2800	2650
11R22.5	16	FREEWAY DRIVE	22.00	27.7	8.25	TL	146/143L	1061	272	830	830	3000	2725
11R24.5	14	FREEWAY DRIVE	21.50	27.1	8.25	TL	146/143L	1106	268	720	720	3000	2725
11R24.5	16	FREEWAY DRIVE	21.50	27.1	8.25	TL	149/146L	1106	268	830	830	3250	3000
295/75R22.5	14	FREEWAY DRIVE	22.00	27.7	9.00	TL	144/141L	1024	290	760	760	2800	2575
295/75R22.5	16	FREEWAY DRIVE	22.00	27.7	9.00	TL	146/143L	1020	288	830	830	3000	2725
285/75R24.5	14	FREEWAY DRIVE	21.50	27.1	8.25	TL	144/141L	1059	272	760	760	2800	2575
285/75R24.5	16	FREEWAY DRIVE	21.50	27.1	8.25	TL	147/144L	1059	272	830	830	3075	2800



**TYPE MODEL-**  
**B878 /G828/A70I**



Suitable for drive position  
Designed for mid-long distance transportation on paved road at high speed

- Directional strong pattern block provides excellent driving and braking ability
- Lateral groove design effectively improves self-cleaning and prevents stone drilling
- High strength casing steel cord and reinforced bead provide excellent light load transportation performance
- Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	16	FREEWAY DRIVE	22.00	27.7	8.25	TL	146/143L	1061	272	830	830	3000	2725
12R22.5	18	FREEWAY DRIVE	22.00	27.7	9.00	TL	152/149L	1086	290	930	930	3550	3250
295/80R22.5	16	FREEWAY DRIVE	22.00	27.7	9.00	TL	152/148M	1053	295	850	850	3550	3150
295/80R22.5	18	FREEWAY DRIVE	22.00	27.7	9.00	TL	152/149M	1053	295	900	900	3550	3250
315/80R22.5	18	FREEWAY DRIVE	22.00	27.7	9.00	TL	154/151M	1081	312	830	830	3750	3450
315/80R22.5	20	FREEWAY DRIVE	22.00	27.7	9.00	TL	157/154L	1081	312	900	900	4125	3750
315/80R22.5	20	FREEWAY DRIVE	22.00	27.7	9.00	TL	157/154L	1081	308	900	900	4125	3750





**NEW MODEL-**  
**A702**



Suitable for drive position  
Designed for mid-long distance transportation on paved road at high speed

- ▶ Special Aggressive tread design with open shoulder provides excellent traction
- ▶ Lateral groove design effectively improves self-cleaning and prevents stone drilling
- ▶ Independent pattern block provides powerful driving and braking ability
- ▶ Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
315/80R22.5	20	FREEWAY DRIVE	24.80	31.2	9.00	TL	157/154K	1090	316	900	900	4125	3750



**TYPE MODEL-**  
**A888+**




Suitable for drive position  
Designed for mid-long distance transportation on paved road at high speed

- ▶ Widened tread enhances drive and braking performance, more suitable for single drive axle trucks
- ▶ Strengthening ribs between patterns blocks significantly strengthen tread rigidity, improve tear-resistance of tread bottom and avoid block crack
- ▶ Heat emission holes on shoulders effectively improve tread heat emission
- ▶ Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	FREEWAY DRIVE	22.80	28.7	9.00	TL	152/149L	1085	293	930	930	3550	3250
315/80R22.5	20	FREEWAY DRIVE	24.00	30.2	9.00	TL	157/154K	1080	316	900	900	4125	3750



**TYPE MODEL-**  
**A88**



Suitable for drive position  
Designed for mid-long distance transportation on paved road at high speed

- ▶ Independent pattern block provides powerful driving and braking ability
- ▶ Creative stone ejector effectively prevents stone clamping
- ▶ Strengthening ribs between pattern blocks strengthen tread, enhance tear-resistance for tread bottom and reduce tread chunking
- ▶ Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	FREEWAY DRIVE	22.00	27.7	9.00	TL	152/149L	1089	293	930	930	3550	3250



**OFF ROAD**

A66+

A669

A903

A905





**NEW MODEL-**  
**A803**



Suitable for ON & OFF tires for rear axle of dump truck

- ▶ Optimized and curved lug type design to prevent stone holding.
- ▶ Designed to have maximum tread width to achieve excellent driving performance.
- ▶ The double curvature design of the ground surface greatly improves mileage performance.

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	ON OFF DRIVE	23.00	29.0	9.00	TL	152/149K	1094	293	930	930	3550	3250



**NEW MODEL-**  
**A805**



Specially engineered for the toughest road conditions & extra-heavy load  
Designed for both line haul and regional applications

- ▶ Self-cleaning pattern blocks provide powerful traction and braking ability on & off roads
- ▶ Cutting edge tread compound provides excellent cut & chip resistance
- ▶ Improved carcass steel cord and belt design maximize retreadability and extend tire life
- ▶ Reinforced bead guarantees excellent performance on various road conditions

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11R22.5	16	ON OFF DRIVE	23.0	29.0	8.25	TL	148/145K	1062	276	830	830	3150	2900



**NEW MODEL-**  
**A807**



Suitable for drive position  
Designed for mid-short distance heavy load transportation on mixed road conditions at mid-low speed

- ▶ Self-cleaning pattern blocks provide powerful traction and braking ability on & off roads
- ▶ Cutting edge tread compound provides excellent cut & chip resistance
- ▶ Improved carcass steel cord and belt design maximize retreadability and extend tire life
- ▶ Reinforced bead guarantees excellent performance on various road conditions

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12.00R24	18	ON OFF DRIVE	19.5	24.6	8.50	TT	158/155K	1229	308	830	830	4250	3875
12.00R24	20	ON OFF DRIVE	19.5	24.6	8.50	TT	160/157K	1229	308	900	900	4500	4125



**REGIONAL**

A9

A959

B875

A919





**TYPE MODEL-**  
**A9 /E900**



Suitable for all positions  
Designed for mid-short distance heavy load transportation on paved road at mid-low speed

- > Strong triple lines pattern design effectively enhance driving and braking performance on various of road conditions
- > Optimized tread formula provides excellent cut-resistance and tear-resistance
- > Reinforced carcass steel cord and bead promotes even stress distribution, reduce deformation curve
- > Low heat generation, more suitable for mid-short distance transportation under heavy load condition

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
9.00R20	16	REGIONAL ALL	15.50	19.5	7.00	TT	144/142H	1019	260	900	900	2800	2650
10.00R20	18	REGIONAL ALL	16.00	20.2	7.50	TT	149/146J	1054	278	930	930	3250	3000
11.00R20	18	REGIONAL ALL	16.50	20.8	8.00	TT	152/149K	1080	286	930	930	3550	3250
12.00R20	18	REGIONAL ALL	17.00	21.4	8.50	TT	154/151K	1120	310	830	830	3750	3450
12.00R20	20	REGIONAL ALL	17.00	21.4	8.50	TT	156/153K	1120	310	900	900	4000	3650
13R22.5	20	REGIONAL ALL	17.00	21.4	9.75	TL	156/153K	1120	316	930	930	4000	3650



**NEW MODEL-**  
**A802**




Suitable for drive position  
Designed for mid-short distance heavy load transportation on mixed road conditions at mid-low speed

- > Open shoulder structure provides tire with good ability of water evacuation as well as anti-hydroplaning
- > Streamline pattern designed by computer simulation effectively ejects stones and prevents possible damage to the bottom of grooves
- > Directional mixed pattern provides tire with excellent traction and brake performance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
315/80R22.5	20	ON OFF DRIVE	24.50	30.9	9.00	TL	157/154J	1070	316	900	900	4125	3750



**TYPE MODEL-**  
**A919**



Suitable for trailer positions  
Designed for mid-long distance transportation on paved road at high speed

- > Three zigzag pattern design provides excellent driving and braking ability
- > Strong pattern block more suitable for mixed road conditions
- > High strength casing steel cord and reinforced bead provide excellent light load transportation performance
- > Optimized tread formula provides excellent wear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	REGIONAL TRAILER	16.50	20.8	9.00	TL	152/149L	1081	293	930	930	3550	3250



**TYPE MODEL-**  
**D909**



Suitable for drive position  
Designed for mid-short distance heavy load transportation on mixed road conditions at mid-low speed

- > 0 degree structure on shoulder, provides high quality and performance under heavy load conditions
- > Solid block pattern on shoulder, optimized longitudinal and lateral groove design, provide superior grip performance, safe, durable and powerful
- > Low heat generation tread recipe, open shoulder design, reduce shoulder separation effectively

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11.00R20	18	ON OFF DRIVE	19.00	23.9	8.00	TT	152/149K	1080	284	930	930	3550	3250
12.00R20	18	ON OFF DRIVE	20.60	26.0	8.50	TT	154/151K	1119	308	830	830	3750	3450
12.00R20	20	ON OFF DRIVE	20.60	26.0	8.50	TT	156/153K	1119	308	900	900	4000	3650





**TYPE MODEL-**  
**C958 /D90I**



Suitable for drive position  
Designed for short distance transportation on mixed road conditions at mid-low speed

- > Contiguous lateral big block pattern provides powerful driving and braking ability
- > Stone ejector at groove bottom avoids crown cut
- > Optimized tread formula provides excellent cut-resistance and tear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	ON OFF DRIVE	18.50	23.3	9.00	TL	152/149K	1080	290	930	930	3550	3250
11.00R20	18	ON OFF DRIVE	18.50	23.3	8.00	TT	152/149K	1080	284	930	930	3550	3250
12.00R20	18	ON OFF DRIVE	18.60	23.4	8.50	TT	154/151K	1115	308	830	830	3750	3450
12.00R20	20	ON OFF DRIVE	18.60	23.4	8.50	TT	156/153K	1115	308	900	900	4000	3650



**TYPE MODEL-**  
**A928**



Suitable for drive position of dumper  
Designed for mid-short distance transportation on mixed road conditions

- > Lateral strong pattern blocks provide excellent driving and braking ability, more suitable for mining and construction application
- > High strength casing steel cord and reinforced bead provide excellent light load transportation performance
- > Optimized tread formula provides excellent cut-resistance and tear-resistance

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	ON OFF DRIVE	24.00	30.2	9.00	TL	152/149K	1096	293	930	930	3550	3250
295/80R22.5	18	ON OFF DRIVE	21.00	26.5	9.00	TL	152/149K	1050	295	900	900	3550	3250



**TYPE MODEL-**  
**B875 /T8II**



Suitable for trailer positions  
Designed for mid-long distance heavy load transportation on mixed road conditions at mid-low speed

- > Unique zigzag pattern design provides superior driving and avoids uneven wear
- > Optimized contact ground design increases uniform wear and provides longer service life
- > Low heat generation tread recipe, wider shoulder design, reducing shoulder separation effectively

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
7.50R16LT	14	REGIONAL TRAILER	13.00	16.4	6	TT	122/118L	803	212	670	670	1500	1320
11R22.5	16	REGIONAL TRAILER	15.00	18.9	8.25	TL	146/143L	1047	272	830	830	3000	2725
12R22.5	12	REGIONAL TRAILER	15.00	18.9	9.00	TL	143/141L	1074	290	620	620	2725	2575
12R22.5	18	REGIONAL TRAILER	15.00	18.9	9.00	TL	152/149L	1074	290	930	930	3550	3250
315/80R22.5	18	REGIONAL TRAILER	16.00	20.2	9.00	TL	154/151M	1076	310	830	830	3750	3450
315/80R22.5	20	REGIONAL TRAILER	16.00	20.2	9.00	TL	157/154L	1076	310	900	900	4125	3750



**TYPE MODEL-**  
**A959**



Suitable for all positions  
Designed for mid-long distance transportation on paved road at mid-low speed

- > Four longitudinal zigzag grooves design provides excellent high speed and anti-skidding performance
- > The V-shaped groove bottom design effectively prevents stone-drilling and possible damage
- > Optimized tread formula effectively increases wear-resistance and provides excellent service mileage
- > Low heat generation, more suitable for mid-short distance transportation under heavy load condition

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
11.00R20	18	REGIONAL ALL	15.00	18.9	8.00	TT	152/149K	1078	282	930	930	3550	3250



**ON & OFF**

- A958            B958
- C958            A928
- A802            D909
- A803            A805
- A807



**TYPE MODEL-**  
**A958 /A801**



Suitable for drive position  
Designed for mid-short distance heavy load transportation on mixed road conditions at mid-low speed

- > Non-contiguous pattern block provides powerful driving and braking ability
- > Optimized tread formula provides excellent cut-resistance and tear-resistance
- > Reinforced carcass steel cord and bead promote even stress distribution, reduce deformation curve

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
12R22.5	18	ON OFF DRIVE	19.00	23.9	9.00	TL	152/149K	1085	293	930	930	3550	3250
13R22.5	20	ON OFF DRIVE	19.00	23.9	9.75	TL	156/153K	1124	316	930	930	4000	3650
10.00R20	16	ON OFF DRIVE	18.00	22.7	7.50	TT	146/143K	1058	278	830	830	3000	2750
10.00R20	18	ON OFF DRIVE	18.00	22.7	7.50	TT	149/146K	1058	278	930	930	3250	3000
11.00R20	18	ON OFF DRIVE	19.00	23.9	8.00	TT	152/149K	1085	286	930	930	3550	3250
12.00R20	18	ON OFF DRIVE	19.00	23.9	8.50	TT	154/151K	1124	310	830	830	3550	3250
12.00R20	20	ON OFF DRIVE	19.00	23.9	8.50	TT	156/153K	1124	310	900	900	4000	3650



**TYPE MODEL-**  
**B958**



Suitable for drive position of dumper  
Designed for short distance heavy load transportation on mixed road conditions at low speed

- > Non-contiguous pattern block provides powerful driving and braking ability
- > Strengthening ribs between pattern blocks significantly strengthen tread rigidity and durability
- > Optimized tread formula provides excellent cut-resistance and tear-resistance under heavy load
- > Reinforced carcass steel cord and bead promote even stress distribution, reduce deformation curve

Tire Size	PR	Pattern Description	Tread Depth		Rim	Tube Type	L.I./S.S.	Over Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
			mm	1/32 Inch						Single	Dual	Single	Dual
10.00R20	16	ON OFF DRIVE	21.80	27.5	7.5	TT	146/143J	1064	278	830	830	3000	2725
10.00R20	18	ON OFF DRIVE	21.80	27.5	7.5	TT	149/146J	1064	278	930	930	3250	3000
11.00R20	18	ON OFF DRIVE	21.00	26.5	8.00	TT	152/149J	1080	286	930	930	3550	3250
12.00R20	18	ON OFF DRIVE	22.00	27.7	8.50	TT	154/151J	1121	310	830	830	3750	3450
12.00R20	20	ON OFF DRIVE	22.00	27.7	8.50	TT	156/153J	1121	310	900	900	4000	3650